



Different states, counties, cities and areas have their own VOC regulations and requirements and necessitate use of complying products polycoat products manufacture products with different VOC's ranging from 100 to 340 gms/liter VOC to comply with a wide range of requirements. It is the responsibility of the user to ensure that they are using correct products that comply with VOC regulations at the place of installation. Refer technical data sheets for each product for details on VOC. Polycoat products assume no liabilities of any kind with regard to the selection of appropriate products.

FOR AREAS WITH MORE STRINGENT REQUIREMENTS, CONSIDER USING THE FOLLOWING SUBSTITUTES:

PRODUCT	PRODUCT SUBSTITUTE
Polyprime® 2180	Polyprime® 2180 SC
PC-220	PC-220 SC
PC-440	PC-440 SC
Polyglaze® 100 & 100 C	Polyglaze® 100 SC
Polyglaze® 400 & 400 C	Polyglaze® 400 SC
Polyglaze® 400 FR & 400 C-FR	Polyglaze® 400 SC-FR
Polyglaze® AL-50	Polyglaze® AL-50 SC
Polyglaze® AR	Polyglaze® AR-OF
Poly-I-Gard™ 246	Poly-I-Gard™ 246 SC

Not responsible for typographical errors. Graphical depictions and architectural details are for convenience only and may not fully represent all pertinent details. Accordingly, they are not to be relied upon in lieu of information from application guidelines, technical data sheets, system specifications, and safety data sheets. Products are typically applied at a suggested rate of 100 square feet per gallon, but actual usage rate will vary significantly depending upon application techniques, site conditions, porosity, and texture of the substrate.